



J2 900cx

Integrated Touchscreen Computer

900cx Series

The 900cx series from J2 sets the benchmark for integrated high performance touch screen systems by delivering unprecedented functionality, durability, quality, and affordability.

The 900cx represents leading edge technology for the most demanding point-of-sale; point-of-service; and point-of-information device markets and can meet any price/performance budgets.

The 900cx series provides advanced POS technology to improve customer transactions. This industry standard open platform can operate a broad range of operating systems and industry standard peripherals. The 900cx integrated system is designed to withstand harsh environments including retail and foodservice, and kiosk. The 900cx features Intel Celeron, Pentium III, P4 CPUs and ELOTouch touchscreens.

Dependability and durability have not been compromised in this sleek and elegant design to provide an exceptional investment with a long duty cycle to maximize your return on investment.

KEY FEATURES:

- 12.1" or 15" TFT/Active Matrix LCD
- Adjustable Tilt Angle 0° ~ 60°
- Smart Card Reader (option)
- PCMCIA Slot (option)
- +24V DC Output For Thermal Printer
- 6 x Com Ports
- 4 x USB
- 2 x Cash Drawer Ports
- Integrated Power Supply
- Internal Speakers
- 3-Track MSR (option)
- VFD Customer Display (option)
- Secondary LCD Display Option (8.4", 10.4", or 12.1")
- OPOS Drivers



The 900cx can be web enabled for e-commerce. This system can enhance the customer experience with a secondary LCD, providing full motion video. This feature can also speed up the return on your investment through third-party advertising.





Integrated Touchscreen Computer



Mainboard

- CPU **Intel Celeron, Pentium III, P4**
- Core Logic **SIS 650**
- Memory **128 MB DDR SDRAM; Supports up to 2 GB**
- FSB **66/100/133 Mhz**
- Video **AGP 4X; Up to 64 MB**

LCD Touch Display

- LCD **12.1" TFT LCD; 800 x 600 Resolution
15" TFT LCD; 1024 x 768 Resolution**
- Touchscreen **5-wire resistive membrane**
- Brightness **150 ~ 180 cd/m²**

Storage

- Compact Flash **Socket supported**
- PCMCIA **Option (supports Type I & II)**
- Hard Disk **3.5" 20+ GB**
- FDD **External connector**
- CD-ROM **One slim CD-ROM bay**

I/O Ports

- Serial **6 (4 external with +5/12V DC)**
- USB **4**
- PS/2 **2 (keyboard & mouse)**
- LAN **10/100 Base T**
- Parallel **1**
- Cash Drawer **2 (12/24V DC)**
- Audio **Line-in, line-out**
- Printer **24V DC-OUT**

Other

- Dimensions **920cx: 11.9" x 11.9" x 7.9"**
- Temperature **0°C-40°C**
- EMI **CE/FCC Class A**
- Power **Internal 150W**

Options

- MSR **3 Tracks Keyboard (standard)**
- Customer Display **VFD Type**
- LCD Display **External VGA support**



Global Headquarters

J2 Retail Systems, Ltd.
J2 House
Clayton Road
Birkwood
Warrington, WA3 8BP
United Kingdom
info@j2retailsystems.com
www.j2retailsystems.com
Tel: 44 (0) 1925 817903
Fax: 44 (0) 1925 813800

US Headquarters

J2 Retail Systems, Inc.
2691 Dow Avenue
Building A
Tustin, CA 92780
USA
info@j2retailsystemsusa.com
www.j2retailsystemsusa.com
Tel: 714 469 3111
Fax: 714 469 3133

All trademarks and copyrights belong to their respective companies.

